

### Description

**elin CDO 60** is a high-performance 60 BN SAE 50 cylinder lubricant particularly intended for lubricating the cylinders of the latest generation crosshead engines using low sulphur fuel **(from 1,0 to 3,0 wt% sulphur)**.

**elin CDO 60** is blended from highly refined, paraffinic base oils and carefully selected additives to provide superior ring and liner wear protection and excellent piston cleanliness in crosshead engines.

### Main Performance Features

1. Wear Protection
2. Detergent/Dispersant Properties
3. Excellent Lubrication Properties
4. Storage Stability
5. Fully compatible with all the mineral cylinder oils

### Typical uses

**elin CDO 60** is recommended for the cylinder lubrication of all crosshead marine diesel engines continuously using low to high sulphur fuel and operating at high specific power outputs and high thermal loads or under slow steaming conditions.

### Oil feed rates:

Follow the engine manufacturers recommended cylinder oil feed rates as the minimum and also take into consideration the fuel oil sulphur content level.

### (\*) Typical Characteristics

SAE	50
Density at 15°C, Kg/l	0,930
Kin. Viscosity at 100°C, cSt	21,0
Kin. Viscosity at 40°C, cSt	247
Flash point (C.O.C.), °C	270
Pour Point, °C	-9
Base Number, mg KOH/g	60
Sulphated ash, mass %	7,0

(\*) (The above figures are typical of those obtained within normal production tolerances, and do not constitute a specification)

